



STATEMENT OF HAZARDOUS NATURE

Non Hazardous According to Criteria of Work safe Australia

IDENTIFICATION

Product Name:	Liquid Intelligents 220
Chemical Name:	Engine Flushing Lubricant Additive.
Other Names:	None Assigned
Manufacturer's Product Code:	220
UN Number:	None Assigned.
Dangerous Goods Class	None Assigned.
Subsidiary Risk[s]:	None Assigned.
Hazchem Code:	None Assigned.
EPG NO:	None Assigned.
Poisons Schedule Number:	None Assigned.
Toxic and Hazardous Ingredients:	None
Uses:	Engine Flushing Lubricant Additive.

PHYSICAL DESCRIPTION AND PROPERTIES

Colour:	Fluoro - Green
Appearance:	Oily Liquid
Form:	Liquid
Boiling Point:	>290°C:
Melting Point:	Not Applicable
Vapour Pressure:	mm Hg: <0.01.
Specific Gravity:	kg/L @ 15.0°C : 0.898
Volatiles:	Not Applicable
Evaporation Rate:	Not Applicable
Vapour Density:	Not Applicable
Odour:	New engine oil odour
Solubility in Water:	Nil @ 20°C

FLASH POINT

Solvent:	Not Applicable
Lubricant residue:	>190°C
Flammability Limits:	Not Applicable
Auto ignition Temperature:	>450°C

MATERIAL SAFETY DATA SHEET**OTHER PROPERTIES**

Hazardous Polymerisation: Does Not Occur

INGREDIENTS

Chemical Name	CAS Number	Proportion
Highly refined Mineral oils (Does not contain PCB's)	64742-65-0	83-87%
Proprietary Oxidation and Rust Inhibitors, Dispersants, Detergents, Anti-Wear, PPD.	Include on US TSCA Inventory	13-17%

HEALTH HAZARD INFORMATION**HEALTH EFFECTS:****Acute:**

Swallowed: If swallowed and person is conscious give water or milk. Ingestion or subsequent vomiting may result in its aspiration, which could cause pneumonitis.

Skin: Prolonged or frequent contact may cause irritation or skin cracking.

Inhaled: Vapour or mist at concentrations exceeding ACGIH TLV may be irritating to the respiratory tract.

Chronic:

LC 50: No Data

LD 50: No Data

FIRST AID:

Swallowed: Do not induce vomiting. Aspiration of the fluid may cause lung injury (pneumonitis). Call a Doctor immediately.

Skin: Wash thoroughly with soap and water.

Eyes: Flush with water for 15 minutes, at least with eyelids open.

Inhaled: If respiratory irritation occurs move person to fresh air. If irritation continues call a Doctor.

ADVICE TO DOCTOR: Refer First Aid above.

PRECAUTIONS FOR USE

Exposure Standards: The ACGIH TLV for mineral oil mists is 5mg/m³ for a daily 8 hours exposure.

Engineering Controls: As for oil mists

Personal Protection: Avoid prolonged or frequently repeated contact. Wash skin thoroughly with soap and water after

MATERIAL SAFETY DATA SHEET

Flammability: contact. Use safety glasses and neoprene or nitrile rubber gloves for frequent contact.
Product is not classed flammable. Flash Point greater than 245°C
Product may support combustion. Do not store with strong oxidants.

SAFE HANDLING INFORMATION

Storage and Transport: Store in steel or HDPE plastic drums. Store away from strong oxidising agents. Refer Dangerous Goods Class 5:1

Storage Temperature: Store in a cool dry place.

UN Class: None Assigned

Packaging Group: None Assigned

UN Number: None Assigned

EPG Number: None Assigned

Correct Shipping Name: Engine Flushing Lubricant Additive.

Spills and Disposals: Absorbents such as cat litter, clays and rags to clean up spills. Dispose of absorbent in approved disposal containers.

Fire/Explosion Hazard: Not a fire hazard. Auto ignition temperature is in excess of 450°C. Should fire occur, however, use dry chemical, foam or carbon dioxide to extinguish.

Hazchem Code: None Assigned.

Extinguishant: Dry Chemical, Foam Or Carbon Dioxide.

DANGER OF VIOLENT REACTION OR EXPLOSION: No

Protective Clothing; Applicable to degree of fire.

Appropriate Measures; No Data

Evacuate; Not Normally

OTHER INFORMATION:

Agricultural Engine Lubricant is not expected to present environmental problems other than those associated with oil spills.
High temperature thermal decomposition may promote formation Oxides of Carbon, Nitrogen, Sulphur and Phosphorus.



MATERIAL SAFETY DATA SHEET

CONTACT POINT:

**Peter Maher
Liquid Intelligents Pty Ltd
14 Underwood Ave Botany, NSW, 2019, Australia
Ph 02-9700 0880. Fax 02-9700 0881.
Mob 0423 593 261**

**24 Hour Emergency Tel No.
Emergency Services**

**Above Mobile
Dial 000**

Disclaimer:

Liquid Intelligents, provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. This document is intended only as a guide to the appropriate precautionary handling of the material by a properly trained person using this product. Individuals receiving the information must exercise their independent judgment in determining its appropriateness for a particular purpose. LIQUID INTELLIGENTS, MAKES NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESS OR IMPLIED, INCLUDING WITHOUT LIMITATION ANY WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE WITH RESPECT TO THE INFORMATION SET FORTH HEREIN OR THE PRODUCT TO WHICH THE INFORMATION REFERS. ACCORDINGLY, LIQUID INTELLIGENTS WILL NOT BE RESPONSIBLE FOR DAMAGES RESULTING FROM USE OF OR RELIANCE UPON THIS INFORMATION.
