



STATEMENT OF HAZARDOUS NATURE

Non Hazardous According to Criteria of Work safe Australia

IDENTIFICATION

Product Name:	Liquid Intelligents 230
Chemical Name:	Stop Leak Seal Expander and Conditioner.
Other Names:	None Assigned.
Manufacturer's Product Code:	230.
UN Number:	None Assigned.
Dangerous Goods Class	None Assigned.
Subsidiary Risk[s]:	None Assigned.
Hazchem Code:	None Assigned.
EPG NO:	None Assigned.
Poisons Schedule Number:	None Assigned.
Toxic and Hazardous	
Ingredients:	Sulphur dioxide.
Uses:	Repairs and prevent rubber oil seal leakage in lubrication systems.

PHYSICAL DESCRIPTION AND PROPERTIES.

Colour:	Red.
Appearance:	Light red clear liquid.
Form:	Liquid.
Boiling Point:	>200°C.
Melting Point:	Not Applicable.
Vapour Pressure:	Not Determined.
Specific Gravity:	0.88 at 15.6°C
Volatiles:	Unknown.
Evaporation Rate:	Not Determined.
Vapour Density:	Not Determined.
Odour:	Sulphur Smell.
Solubility in Water:	Insoluble

FLASH POINT

Solvent:	Nil.
Lubricant residue:	230°C
Flammability Limits:	Unknown
Auto ignition	
Temperature:	No Data.

MATERIAL SAFETY DATA SHEET**INGREDIENTS**

Chemical Name	CAS Number	Proportion
Highly refined Mineral oils (Does not contain PCB's)	64742-65-0	83-87%
Sulfur dioxide	7446-09-5;	OSHA PEL 2 ppm (TWA), OSHA STEL 5 ppm; ACGIH TLV 2 ppm

HEALTH HAZARD INFORMATION**HEALTH EFFECTS:****Acute:**

Swallowed:	The LD50 in rats is >5000 mg/Kg. Based on actual data.
Skin:	May cause skin irritation. Based on actual data.
Eyes:	Not expected to cause eye irritation. Based on actual data.
Inhaled:	Short-term exposures to sulphur dioxide above 50-100 ppm can be dangerous and above 400-500 ppm, immediately life threatening.

Chronic:

LC 50:	No Data.
LD 50:	In rabbits is >20000 mg/Kg. Based on actual data.

FIRST AID:

Swallowed:	DO NOT INDUCE VOMITING if conscious, give 2 glasses of water. Get immediately medical attention.
Skin:	Wash with soap and water. Remove contaminated clothing. Get medical attention if irritation develops. Launder contaminated clothing before reuse.
Eyes:	Flush with water at least 15 minutes. Get medical attention if eye irritation develops or persists.
Inhaled:	Remove exposed person to fresh air if adverse effects are observed.

FIRST AID FACILITIES:**ADVICE TO DOCTOR:** Treat symptomatically.**PRECAUTIONS FOR USE**

Exposure Standards:	The ACGIH TLV for mineral oil mists is 5mg/m ³ for a daily 8 hours exposure. The ACGIH TLV for Sulphur dioxide is 2 mg/m ³ for a daily 8 hours exposure.
Engineering Controls:	As for oil mists
Personal Protection:	Avoid prolonged or frequently repeated contact. Wash skin thoroughly with soap and water after contact. Use safety glasses and neoprene or nitrile rubber gloves for frequent contact.

MATERIAL SAFETY DATA SHEET

Flammability: Product is not classed flammable. Flash Point greater than 190°C
Product may support combustion. Do not store with strong oxidants.

SAFE HANDLING INFORMATION

Storage and Transport: Store away from foodstuffs.
Use dry, security rated storage as used for schedule 6 poison categories.
Transport as per dangerous goods regulations.

Storage Temperature: Material is normally stable at moderately elevated temperatures and pressures.

UN Class: None Assigned.
Packaging Group: None Assigned.
UN Number: None Assigned.
EPG Number: None Assigned.
Correct Shipping Name: Seal Expander and Conditioner.

Spills and Disposals: Personal Protective Equipment must be worn, see Special Protection Information Section for PPE recommendations. Ventilate area if spilled in confined space or other poorly ventilated areas. Prevent entry into sewers and waterways. Pick up free liquid for recycle and/or disposal. Residual liquid can be absorbed on inert material. Check under Transportation and Labelling (DOT/CERCLA) and Other Regulatory Information Section (SARA) for hazardous substances to determine regulatory reporting requirements for spills.

Fire/Explosion Hazard: Toxic fumes; gases or vapours may evolve on burning or exposure to heat.

Decomposition Products: Smoke, carbon monoxide, aldehydes and other product of incomplete combustion. Under combustion conditions, oxides of Sulphur will be formed.

Hazchem Code: Not Applicable.

Extinguishant: CO₂, dry chemical, alcohol foam. Water can be used to cool and protect exposed material.

DANGER OF VIOLENT REACTION OR EXPLOSION: No

MATERIAL SAFETY DATA SHEET

Protective Clothing: Long sleeve shirt is recommended. Wash contaminated clothing before reuse.

Appropriate Measures: Good Safe Handling Practice.

Evacuate: Not Usually.

OTHER INFORMATION:

Special Precautions: Open container in a well ventilated area. Avoid breathing vapours. Keep containers closed when hot in use. Sulphur dioxide may build up in the vapour space or headspace at temperatures above 100°F (38°C). Wash thoroughly after handling. Launder contaminated clothing before reuse. Empty container contains product residue, which may exhibit hazards of product.

CONTACT POINT:

Peter Maher
 Liquid Intelligents Pty Ltd
 14 Underwood Ave Botany, NSW, 2019, Australia
 Ph 02-9700 0880. Fax 02-9700 0881.
 Mob 0423 593 261

24 Hour Emergency Tel No. **Above Mobile Phones**
Emergency Services **Dial 000**

Disclaimer:

 Liquid Intelligents, provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. This document is intended only as a guide to the appropriate precautionary handling of the material by a properly trained person using this product. Individuals receiving the information must exercise their independent judgment in determining its appropriateness for a particular purpose. LIQUID INTELLIGENTS, MAKES NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESS OR IMPLIED, INCLUDING WITHOUT LIMITATION ANY WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE WITH RESPECT TO THE INFORMATION SET FORTH HEREIN OR THE PRODUCT TO WHICH THE INFORMATION REFERS. ACCORDINGLY, LIQUID INTELLIGENTS WILL NOT BE RESPONSIBLE FOR DAMAGES RESULTING FROM USE OF OR RELIANCE UPON THIS INFORMATION.
