

**DESCRIPTION:**

**Liquid Intelligents 102 is a Ethylene Glycol based (organic technology) Long Life radiator coolant.** Liquid Intelligents 102 Long Life Coolant protects against corrosion in all cooling systems.

Liquid Intelligents 102 **contains 93% Mono Ethylene Glycol and 10% Organic Inhibitors.** Liquid Intelligents 102 is dyed **GREEN**

**CHARACTERISTICS:****Antiboil**

Liquid Intelligents 102 when mixed at a 30% solution in water, with a 15 psi pressure cap on a closed cooling system (radiator) increases the boiling point to 126 C, when mixed at a 50% solution in water, with a 15 psi pressure cap on a closed system increases the boiling point to 130 C.

**Antifreeze**

Liquid Intelligents 102 when mixed as a 30% solution in water drops the freeze point to minus 24 C, when mixed as a 50% solution in water drops the freeze point to minus 37 C.

**Corrosion Inhibiting Properties**

The organic anti-corrosion additives used in Liquid Intelligents 102 prevent corrosion damage to valuable internal engine components no matter how many different types of metal are present in your cooling system. In the ASTM D1384 glassware test, incorporated in the Australian & New Zealand AS/NZ2108.1.1997 (Type A) performance standards, Cast Aluminium may loose up to -15mg of weight through corrosion and still pass. Liquid Intelligents 102 when subjected to the same test only lost less than, 1mg, showing Liquid Intelligents 102 anti-corrosion will completely protect the internals of a cooling system.

**Extended Service Interval**

Liquid Intelligents 102 long life coolant protects cooling systems for a minium of 3 Years or 100,000 km's. This protection extends to petrol, diesel and gas combustion engines in cars, light commercials, trucks, buses, earth moving equipment and slow moving vehicles

**Recommendations**

Liquid Intelligents 102 Long Life Coolant meets and exceeds the following OEM specifications.

General Motors GM 1825M	Australian Standard AS/NZS 2108.1.1997
General Motors GM 6277M	Ford SED-M97B49-A
Japanese JIS K2234 LLC	Ford SED-M97B49-A
Japanese SAE J I034	Ford WSS-M97B44-C
Japanese JASO M325 LLC	BS 6580 (British Standard)
UNE 26-361-88/1	FVV Heft R443 (Germany)

## SERVICE BULLETIN

NATO S-757	BT-PS-606A (MIL Belgium)
Caterpillar EC-1	E/L-1415b (MIL Italy)
Komatsu	Renault
Navistar	Volvo (Reg No 260) Spec.No. 1286083
Man 324	BMW N600 69.0
Mercedes Benz DBL 7700	Cummins 90 T8-4
Detroit Diesel/Perkins	ADE
Volkswagen VW TL774D	Opel/GM
Audi/SEAT/Skoda TL774C	Mack-RVI
ISUZU	DAF-Leyland 74001
Afnor R15-601	Onorm V5132
BR 637	DCEA 615 (MIL-France)
FSD 8704 (MIL Sweden)	Mitsubishi ES-X64216
Honda	Hyundai
Mazda MES 121C	Toyota TS K2601 G
Daihatsu	Subaru

The above spec's include Holden's VN to VY V6 & V8 Commodores.

LIQUID INTELLIGENTS PTY LIMITED  
SYDNEY AUSTRALIA  
DISTRIBUTED BY:

