

**DESCRIPTION:**

Liquid Intelligents 240 Radiator Flush. Is a liquid chemical solution which when added to water of cooling systems completely dissolves and liquidates all ferrous and mineral scale (rust). Will not damage metal, rubber or plastic. Cleans while you drive. **Application Ratio for 240, 50ml per litre.**

CHARACTERISTICS:**How To Apply**

Drain Radiator and fill with clean water.

Pour Mainlube Radiator Flush into the radiator then operate machine as normal. Cleaning action begins at once.

On New Machinery

The action is completed in approximately 3 hours after which the cooling system **MUST BE DRAINED** and thoroughly flushed with clean fresh water then refilled with fresh water.

On Old Machinery

Where the rust is deep the action is completed in approx 6-8 hours then the cooling system **MUST BE DRAINED** and thoroughly flushed with clean fresh water then refilled with fresh water.

In badly corroded systems, reverse flushing is recommended to remove all loosened scale and obtain maximum results with Liquid Intelligents 240 Radiator Flush.

After Flushing

Old And New Machinery Could Then Before Operating, Have 5% Liquid Intelligents 108 Radiator Corrosion Inhibitor And Water Pump Lubricant Added To Prevent Rapid Re-rusting Of Cooling System And Future Scale Build up.

APPLICATION RATIO: 1:20 5% OR 500mls TO 10 Litres OF COOLANT

Liquid Intelligents 240

Radiator Flushing Solution. This product contains

0.50 W/W Sodium Dichromate, 0.20% Sulphamic Acid, Activators and Wetting Agents.

CAUTION:

This product contains Acid, if accidental skin contact occurs 240 will cause burning on cuts or broken skin.

IN EMERGENCY

EXTERNAL-Flush with running cold water for 15 Minutes.

INTERNAL-Give mild solution of bicarbonate of soda, milk of magnesia or white of eggs beaten in water.

EYES-Flush liberally with cold water for 15 minutes.

LIQUID INTELLIGENTS PTY LIMITED
SYDNEY AUSTRALIA
DISTRIBUTED BY:

