



DESCRIPTION:

Liquid Intelligents 241 Car Radiator Systems Stop Leak. For immediate stoppage of small puncture and crack leaks in car recirculated heating and cooling systems. Application Ratio 200 ml per 5 Litres.

CHARACTERISTICS:

Liquid Intelligents 241 is a specialised non-toxic organic biodegradable cellulose derived stop leak additive package. Liquid Intelligents 241 is suitable for sealing small puncture and crack leaks found in cooling or heating systems heat exchangers. Liquid Intelligents 241 quickly seals small puncture and crack leaks in the following areas;

- | | | | | |
|--------------------|--------------------|--------------------------------|--------------|----------------|
| Radiators | Hoses | Head Gaskets | Water | Jackets |
| Welsh Plugs | Water Pumps | Cracked Cylinder Blocks | | |

Compatibility

Liquid Intelligents 241 is compatible with all usual anti-freeze, anti-boil and corrosion inhibiting compounds. Caution should be exercised when applying 241 to cooling systems where coolants are filtered as 241 will quickly seal the filter blocking the system.

Self-Healing Action

Liquid Intelligents 241 stop leak additive package's organic fibres are all less than 100 microns in diameter. Once 241's additive package is added to coolant fluid 241 is recirculated around the system as a suspended colloidal mix with the coolant. When a leak occurs the resulting loss of fluid carries 241's fibres into the leak area, as 241's fibres are forced into the leak by the escaping fluid their frayed fibre ends quickly tangle together similar to how Velcro grips. This action quickly stops leaks and where 241 is exposed to the air its binding cement forms a plastic like compound locking the repair in place.

Liquid Intelligents 241 gives good long-term temporary repairs for most systems however 241 is only considered a temporary repair and all leaks should be repaired mechanically correct as soon as possible.

HOW TO APPLY

Before Applying Shake until All Solids Are Suspended.

Depressurised system & add 200ml per system 5 litres. Operate the System as normal and circulate the product delivering it to the repair area blocking the leak.

APPLICATION RATIO: 200 ml per 5 Litres. (25:1)

LIQUID INTELLIGENTS PTY LIMITED
 SYDNEY AUSTRALIA
 DISTRIBUTED BY:

